

**AQUENCE FB 3131**Known as: Adhesin 3131  
August 2019**Description:**

Premium grade EVA for paper converting applications – High speed packet, glue-lap, case & carton making. This adhesive features excellent specific adhesion to most paper coatings.

Meets composition requirements of US FDA 21CFR175.105 "Indirect Food Additives: Adhesives and Components of Coatings". This adhesive is also gluten allergen free.

**Typical Properties:**

<b>Appearance:</b>	White (also available in Pink)
<b>Odour:</b>	Low when wet, dries odourless
<b>Viscosity:</b>	Approx. 850 cP at 23°C
<b>Solids:</b>	Approx. 57%
<b>pH:</b>	Approx. 4.5

**Directions for Use:**

AQUENCE FB 3131 is supplied ready to use and generally applied by roller, wheel, spray, extrusion or nozzle applicators. This adhesive features excellent machining properties. The final bond has good heat and humidity resistance.

**Supplementary Products:**

Previously called Adhesin 3131.

**Clean Up:**

With water whilst wet.

**Storage and Handling:**

Please read the Material Safety Data Sheet for this product BEFORE use.

Product should be stored between 15°C and 30°C on a wooden pallet and kept from freezing. Rotate stock using oldest material first. Keep stock covered to prevent drying out and contamination. Do not mix with other adhesives. Supplied ready for use but can be diluted with water if required.

Please ensure that products classed as a dangerous good are stored in compliance with the applicable regulations.

**Shelf Life:**

Best used within 12 months from date of manufacture when stored under the above conditions in the original unopened containers.

**Last Updated:** 26-08-2015

**DISCLAIMER**

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.

All Technical Data Sheets are uncontrolled documents, copies are not automatically updated