

AQUENCE GA 0202Known as: Adhesin 0202
August 2019**Description:**

Multipurpose EVA for paper converting and graphic arts applications – high speed packet, glue lap, case & carton making, gluing of book spines, book spine restoration and archival work due to its neutral pH. This adhesive features excellent specific adhesion to difficult substrates.

Meets composition requirements of US FDA 21CFR175.105 "Indirect Food Additives: Adhesives and Components of Coatings". This adhesive is also gluten allergen free.

Typical Properties:

Appearance:	White
Odour:	Low
Viscosity:	Approx. 2000 cP @ 23°C
Solids:	Approx. 56 %
pH:	Approx. 7.0 (pH neutral)

Directions for Use:

AQUENCE GA 0202 is generally applied by direct transfer from glue wheel, rotary stencil, extrusion or spray. It can also be applied by brush in book binding applications. This adhesive combines easy brush characteristics with good wet tack. In the field of book restoration, its freedom from plasticiser migration (no added external plasticisers) ensures freedom from embrittlement on ageing. The adhesive contains a preservative to resist bacteria and fungi activity. It is a high quality bookbinding adhesive that gives excellent adhesion to a wide variety of coated and uncoated paper and synthetic cover stocks.

Supplementary Products:

Previously called Adhesin 0202.

Clean Up:

With water whilst wet.

Storage and Handling:

Please read the Material Safety Data Sheet for this product BEFORE use.

Product should be stored between 5°C and 30°C on a wooden pallet and kept from freezing. Use strict stock rotation practices using the oldest batches first. Keep covered when not in use to prevent contamination and drying out. Do not mix with other adhesives. Please ensure that products classed as a dangerous good are stored in compliance with the applicable regulations.

Shelf Life:

Best used within 6 months from date of manufacture when stored under the above conditions in the original unopened containers.

Last Updated: 31-08-2015

DISCLAIMER

Any information given is, to the best of our knowledge, the best currently available, with respect to our products and their use, but it is subject to revision as additional knowledge and experience is gained. Such information is offered as a guideline for experimentation only and is not to be construed as a representation that the material is suitable for any particular purpose or use. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use. This information is not a license to operate under nor is it intended to suggest infringement of any patent. We guarantee a uniform quality standard for this product. The only conditions and warranties accepted by Henkel in relation to this product or process are those implied by either Commonwealth or State statutes.

All Technical Data Sheets are uncontrolled documents, copies are not automatically updated

Henkel Australia Pty Limited
ABN 82 001 302 996

7 Stanton Road
Seven Hills
NSW, 2147, Australia

www.henkel.com
Tel: (+61) 2 9838 6000
Fax: (+61) 2 9624 4434

