

PRODUCT INFORMATION

Nordale Bencha

Double-coated adhesive tape

Features/characteristics

1. Adhesive : Premium acrylic (solvent based) adhesive coated on both sides.
2. Carrier : 1/2 mil (12 μ) clear PET film.
3. Liner : 130 g/m² PE lamination Bleached Kraft paper.
4. Excellent plasticizer migration resistance.
5. Offering a secure bonding result under high temperature condition.
6. Good resistance to solvent, chemicals, UV & heat.
7. Exceptional bonding performance to low surface energy substrates.

Technical data

- | | | |
|------------------------|--------------|--|
| 1. Thickness | : | 0.20 \pm 0.01 mm |
| 2. Tack | : J. Dow No. | 16 |
| 3. Peel Adhesion | : PSTC-3 | 1.8 kg / 25 mm |
| 4. Shear Strength | : PSTC-7 | Over 48 hrs with 1 kg loading on 25 mm x 25 mm |
| 5. Heat Resistance | : | Over 24 hrs with 0.5 kg loading on 25 mm x 25 mm at 80°C |
| 6. Service Temperature | : | - 20 °C ~ 180 °C |

Remarks

All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty. It's essential that the user should evaluate the product for a period of time to determine whether it is fit for a particular purpose and suitable for the user's method of application.
