

TECHNOMELT DM COOL 110 DISPOMELTknown as: Dispomelt Cool 110
August 2019**PRODUCT DESCRIPTION**

TECHNOMELT DM COOL 110 DISPOMELT is a pressure sensitive hotmelt adhesive specifically developed to be suited for nonwovens disposables construction applications featured with good bond strength and creep resistance.

It conforms to the following regulation:
21 CFR 175.105 "ADHESIVE"

APPLICATION

Suggested for all standard slot or nozzle applicators. Operating temperature: 110°C to 130°C, depending on application conditions, machines, substrates, environment, etc.

STORAGE

Store in a dry place where the temperature is below 40°C and the storage life is one year.

PRECAUTIONS


- Do not mix with other adhesives.
- Keep containers and pre-melters covered to avoid contamination.
- Material is applied hot. Appropriate clothing and eye protection should be used.
- Rotate stock - first in, first out.

PHYSICAL PROPERTIES**APPEARANCE**

White cloudy color solid

VISCOSITY

- @ 130°C: Approx. 5000 cps
- @ 120°C: Approx. 8000 cps
- @ 110°C: Approx. 13000 cps
- @ 100°C: Approx. 26500 cps

**SOFTENING POINT**

Approx. 78°C, Ring & Ball

Standard Package

18 kg/carton

**READ PRECAUTIONS AND MSDS
BEFORE USING ADHESIVE**

The information provided herein, especially recommendations for the usage and the application of our products, is based upon our knowledge and experience. Due to different materials used as well as to varying working conditions beyond our control we strictly recommend to carry out intensive trials to test the suitability of our products with regard to the required processes and applications. We do not accept any liability with regard to the above information or with regard to any verbal recommendation, except for cases where we are liable of gross negligence or false intention.